

TECHNICAL SPECIFICATION SHEET

Dolomite Powder

$\text{CaMg}(\text{CO}_3)_2$ · Calcium Magnesium Carbonate

Processed dolomite with consistent CaCO_3 and MgCO_3 content. Available in multiple construction, and paint applications where magnesium content provides functional benefits.

BASE SPECIFICATIONS

Colour	White to light grey
Odour	Odourless
Density	2.85 g/cm ³
pH	9.0 – 9.8 (10% aqueous suspension)
Oil Absorption	20 – 30 g/100g

AVAILABLE GRADES

Grade Code	Particle Size	Brightness (ISO)	Moisture	Typical Applications
LM-DL-30	30 µm (D97)	"e 8 8	"d 0.4 %	Glass manufacturing, Ceramic
LM-DL-75	75 µm (D97)	"e 8 6	"d 0.5 %	Paints, Construction materials
LM-DL-150	150 µm (D97)	"e 8 4	"d 0.6 %	Cement, Road construction, Agricultural lime

All values are batch-average specifications. A batch-specific Certificate of Analysis accompanies every dispatch.

PACKAGING & ORDER

Packaging Options	25 kg HDPE bags · 50 kg HDPE bags · 1 MT jumbo bags · Bulk tanker dispatch
Minimum Order Quantity	10 MT
Quality Documentation	Certificate of Analysis issued per batch
Certification	ISO 9001:2015

ENQUIRIES & SAMPLES

Laxmi FineGrind Industries

G-94 & 95, RIICO Industrial Area, Bidiyad, Makrana, Distt. Kuchaman, Didwana, Rajasthan – 341542

Phone / WhatsApp: +91 9414016501 Email: enquiry@laxmifinegrind.com

GSTIN: 08ABAPC0127F2ZG www.laxmifinegrind.com/products/dolomite